

# Thermographic paint for high temperature applications

## HERP-HT-MWIR-BK-11

### ► **Main features:**

- high emissivity paint
- high mechanical resistance
- opaque
- permanent paint for long-term use
- suitable for uncooled infrared cameras
- resistant to high temperatures up to 1000 °C
- suitable for application in electrical equipment (very low conductivity)
- suitable for industrial furnaces for material temperature treatment, machining of metal parts, heat resistant building materials for high temperatures

### ► **Ingredients:**

- propane, butane, hydrocarbons, isobutane, Kohlenwasserstoffe, C6, Isoalkane, ethylbenzene, butan-1-ol, cyclohexane

### ► **Contents:**

- 400 ml

### ► **Colour**

- black

### ► **Thermal conductivity:**

- 0.52 W/mK (100 °C)
- 0.50 W/mK (300 °C)
- 0.67 W/mK (500 °C)
- 2.05 W/mK (700 °C)

### ► **Other features:**

- coating thickness 150 µm (according to recommended application)
- coating roughness Ra = 3.5 µm, Rz = 25 µm

### ► **Packing:**

- 1 pc minimum

### **Optical properties**

- transmissivity to 1,2 %

### **Dependence of emissivity on the angle**

- for bolometric cameras use the emissivity according to the viewing angle:

Angle (°)	5	10	20	30	40	45	50	60	70	80
Emissivity	0.916	0.916	0.914	0.911	0.904	0.898	0.889	0.862	0.803	0.658

Dates for 1 000 °C, other temperatures are available on the web.



**LablIR®**

phone: +420 377 634 832

e-mail: [paints@labir.cz](mailto:paints@labir.cz)

web: [paints.labir.eu](http://paints.labir.eu)

**LablIR®**